

FC4 Series Observation Thermal Bullet Camera

FC4A thermal bullet camera equipped a 640×512, 12µm pixel pitch thermal detector with a focal length up to 35mm/55mm. It supports tripwire/intrusion detection. It can be used for perimeter protection in critical facilities.





12μm Uncooled Infrared Detector

Adopting the latest $12 \mu m$ uncooled infrared detectors, integrated with advanced infrared imaging algorithms for better image quality.

<u>Long-Range</u> Detection

Supports 35mm/55mm/75mm fixed-focus infrared lenses to meet long-range detection needs.

Intelligent Video Analysis

Support tripwire/intrusion detection, as well as intelligent detection of fire point.

Delatform Integration

Support ONVIF, provide SDK&demo for development; provide NVR and VMS software for application.

Specifications

Technical Specifications	FC460A
	Thermal Module
Detector Type	VOx, uncooled FPA detector
Spectral Range	8~14µm
NETD	≤40mK(@25°C,F#1.0,50Hz)
Resolution	640×512
Pixel Pitch	12µm
Focal Length	35mm/55mm
	Smart Function
Fire Detection	Support
VCA	Support Line crossing&Intrusion detection
2-Way Audio	Support
Linkage Action	Video/ Snapshot/Email
	System Interface
Power	DC 12V±25% / PoE(802.3af)
Network	1×RJ45 10M/100M self-adaptive interface
Audio Input	1×input
Audio Output	1×output
Storage Interface	Micro SD card (up to 256G)
Reset Button	Support
RS485 Interface	1×RS485
	General
Work Environment	-40°C~+60°C;<95%RH
Protection	IP66
Power Consumption	≪4W
Dimensions (mm)	334.7×121.5×104.4
Weight	≤1.5kg

Application Scenarios



Border and Coastal Surveillance Urban High-Altitude Surveillance Critical Infrastructure Protection

River Monitoring

RayThink Technology Co., Ltd. ⊠ sales@raythink-tech.com ♦ +86-19806191838

www.raythink-tech.com

🙎 Room 3002, Building 2, No.5 Wanshoushan Road, Fulaishan Street, Yantai Area of China (Shandong) Pilot Free Trade Zone

• This manual is illustrative only. Technical specifications are subject to change without prior notice.